

Description: Hardline Connector, G052 – 5/8 Male.  
(Measured with Commscope QR540 ASS Cable)

## DATA SHEET

### Electrical

	Specification		Standard
Frequency Range	5 MHz – 3.000 MHz		
Impedance	75 Ω nominal		
	Better Than	Measured – Worst case of 4 measurements	
Return Loss of Assembly	22 dB 17 dB 16 dB 15 dB	≥ 25.1 dB ≥ 20.2 dB ≥ 19.0 dB ≥ 18.3 dB	5 MHz – 500 MHz 500 MHz – 860 MHz 860 MHz – 1.000 MHz 1.000 MHz – 1.750 MHz IEC 61169-1, 9.2.1.4
Gated Return Loss of G052-5/8M	27 dB 22 dB 21 dB 20 dB	≥ 30.0 dB ≥ 25.5 dB ≥ 24.5 dB ≥ 23.3 dB	5 MHz – 500 MHz 500 MHz – 860 MHz 860 MHz – 1.000 MHz 1.000 MHz – 1.750 MHz IEC 61169-1, 9.2.1.4
Insertion Loss of Assembly	0.05 dB 0.07 dB 0.07 dB 0.09 dB	≤ 0.02 dB ≤ 0.04 dB ≤ 0.04 dB ≤ 0.06 dB	5 MHz – 500 MHz 500 MHz – 860 MHz 860 MHz – 1.000 MHz 1.000 MHz – 1.750 MHz
Shielding Effectiveness of assembly (Measured with CoMeT)	Transfer Impedance @ 5 – 30 MHz ≤ 0.7 mΩ/item Screening Attenuation @ 30 – 1.000 MHz ≥ 102.7 dB Screening Attenuation @ 1.000 – 2.000 MHz ≥ 99.9 dB Screening Attenuation @ 2.000 – 3.000 MHz ≥ 94.5 dB Class: A+		IEC 62153-4-3 IEC 62153-4-4 IEC 62153-4-4 IEC 62153-4-4 EN 50117
Shielding Class of G052-58M	Class A++		EN 50117
Common Path Distortion	≤ -110 dBc		ANSI/SCTE 109 2005
Amp. Rating	≤ 15 A. @ 60 V.		
Dielectric Strength	≥ 3 KV.		IEC 61169-1, 9.2.1.6
Insulation Resistance	≥ 29.99 GΩ @ 500 V.		IEC 61169-1, 9.2.1.5

### Environmental

	Specification	Standard
Temperature range Operating	-40°C to +85°C	
Temperature range Installation	-5°C to +50°C	
Sealing Test	IPX8 – 1 meter / 24 hours	IEC 60529
Red Dye		ANSI/SCTE 60
Corrosion Protection		ASTM B 117-94

### Mechanical

	Specification	Standard
Interface	5/8 male	ANSI/SCTE 92
Pull Strength	≥ 125 kgf	ANSI/SCTE 99

### Material and Finish

	Specification	Standard
Housing	NiSn (NITIN) plated Brass	ASTM B605
Compression ring	NiSn (NITIN) plated Brass	ASTM B605
Mandrel	NiSn (NITIN) plated Brass	ASTM B605
Inner Conductor	NiSn (NITIN) plated Brass	ASTM B605
O'ring	EPDM	
Insulator	Polycarbonate & Polyethylene	

In order to continue to supply the best products, PPC reserves the right to change the products and specifications at any time without prior notice.

CoreTel s.r.o.  
K Cintorínu 64  
010 04 Žilina  
Slovenská republika

IČO: 47 744 731  
IČ DPH: SK2024077726

Fio banka a.s. č.ú.:  
EUR: 2500577171/8330  
CZK: 2100577172/2010  
USD: 2400577174/8330

Tel. č.: +421 948 87 55 87  
Tel. č.: +421 948 86 55 86  
Email: coretel@coretel.eu  
Web: www.coretel.eu