

P6IS60ZWMB1/305m - coaxial cable PPC RG6 (4,8) biely, LSZH jacket, 1x shield Al foil + 1x 60% braiding, foam dielectric, 305m drum

Code: 00PPC0096

Coaxial Cable,Inner Conductor:1.02 ± 0.01mm Bare Copper (100%Copper)

+Insulation:4.57 ± 0.05mm Foam PE (FPE)+1St Shield:0.04 ± 0.005mm Bonded AL Foil Tape+2Nd Shield:(4*16)=64*0.16 ± 0.005mm

AL-Mg Alloy wire (Braiding Coverage:60%)+Jacket:6.80 ± 0.10mm LSZH,Jacket Colour:White

Wooden Drum.

■Features

⊙Jacket:LSZH

⊙ Impedance:75 ± 3 Ω

⊙Braiding Coverage:60%

⊙ CCS Rate of Velocity:20%

⊙ Packing:305M / Wooden Drum.

⊙ Jacket Colour:White

Specification

Item	Layer	Material	Specification	Tolerance	Remark
1	Inner Conductor	BC	1.02 MM	±0.01 MM	100%Copper
2	Insulation	Foam PE (FPE)	4.57 MM	±0.05 MM	/
3	1st Shield	Bonded AL Foil Tape	0.04 MM	±0.005 MM	/
4	2nd Shield	AL-Mg Alloy Braiding Wire	(4*16)=64* 0.16MM	±0.005 MM	Coverage:60%

CoreTel s.r.o.
K Cintorínu 64
010 04 Žilina
Slovenská republika

IČO: 47 744 731
IČ DPH: SK2024077726

Fio banka a.s. č.ú.:
EUR: 2500577171/8330
CZK: 2100577172/2010
USD: 2400577174/8330

Tel. č.: +421 948 87 55 87
Tel. č.: +421 948 86 55 86
Email: coretel@coretel.eu
Web: www.coretel.eu

5	3rd Shield	/	/	/	/
6	Jelly	No			
7	Jacket	LSZH	6.80MM	±0.10 MM	White
8	Messenger Wire	/	/	/	/
9	Packing	305M / Wooden Drum			

■ Electronic performance

Type	Attenuation (20 °C)	
	Frequency(Mhz)	BC(≤DB/305M)
00PPC0096 Coaxial Cable	5	5.80
	55	16.01
	211	30.50
	450	44.01
	550	49.04
	750	56.55
	865	61.03
	1000	65.54