



## LSA-PLUS® Series 2 Disconnection Module, 10-pair, PROFIL mounting

- Based on genuine LSA-PLUS® connection technology for use in all xDSL and ADSL2+ circuits
- Offer disconnection points for opening the line, testing in both directions or insertion of graded protection elements
- Robust long-term environmental stability allows both indoor and outdoor installation
- Compatible with accessories such as overvoltage protection magazines, labels, test and -connection cords

### Product Classification

<b>Regional Availability</b>	EMEA
<b>Product Type</b>	Disconnection module
<b>Product Brand</b>	LSA-PLUS®
<b>Product Series</b>	LSA-PLUS Series 2

### General Specifications

<b>Color</b>	Beige
<b>Mounting</b>	PROFIL rods
<b>Pairs, quantity</b>	10
<b>Termination Punchdowns, minimum</b>	200 times
<b>Termination Tool</b>	LSA-PLUS Punchdown tool
<b>Termination Type</b>	IDC

### Dimensions

<b>Width</b>	124 mm   4.882 in
<b>Compatible Conductor Gauge, solid</b>	26–20 AWG
<b>Compatible Conductor Gauge, stranded</b>	26–22 AWG

### Electrical Specifications

<b>Contact Resistance, maximum</b>	1 mOhm
<b>Current Rating, maximum</b>	2 A
<b>Dielectric Strength</b>	3 kV
<b>Insulation Resistance, minimum</b>	50 GOhm

### Material Specifications

# 60891121-02 | 60891121-02

---

<b>Contact Base Material</b>	Brass
<b>Contact Plating Material</b>	Silver
<b>Material Type</b>	Polybutylene terephthalate (PBT)

## Mechanical Specifications

<b>Plug Insertion Life, minimum</b>	250 times
-------------------------------------	-----------

## Environmental Specifications

<b>Operating Temperature</b>	-5 °C to +60 °C (+23 °F to +140 °F)
<b>Storage Temperature</b>	-40 °C to +85 °C (-40 °F to +185 °F)
<b>Relative Humidity</b>	Up to 95%, non-condensing
<b>Environmental Space</b>	Indoor   Outdoor
<b>Flammability Rating</b>	UL 94 V-0

## Packaging and Weights

<b>Packaging quantity</b>	10
<b>Packaging Type</b>	Box   Carton

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on <a href="http://www.commscope.com/ProductCompliance">www.commscope.com/ProductCompliance</a>
ROHS	Compliant

