



Technical datasheet for:

EZA-t 14



General data

| | |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item | Divisible sealing element |
| Description | The divisible and tensile sealing elements EZA-t are reusable and suit for sealing empty and occupied speedpipe. Before 10 bar of blow-in pressure are reached, the integrated safety valve opens. |
| Package unit | 40 Pcs. |

Technical data

| Quality | Value | Unit |
|--------------------------------------------------------------|----------------------|------|
| Material | PolyPhenylenOxid PPO | |
| Dimension | d = 30; L = 43 | mm |
| Sealing range (short term) | EZA-t 14 / 3.0-5.0 | mm |
| | EZA-t 14 / 5.0-6.5 | |
| | EZA-t 14 / 6.5-8.0 | |
| | EZA-t 14 / 8.0-9.5 | |
| Pressure | 0.5 | bar |
| Tensile strength of speedpipe | min. 140 | N |
| Tensile strength to micro-cabel (Ø8.0mm) | min. 60 | N |
| Loading capacity of connecting clamps | min. 750 | N |
| Fire behavior of case half and clamp (DIN EN 13501-1) | E - d2 | |

gabocom is certified by the quality system following DIN EN ISO 9001, the environmental management system DIN EN ISO 14001 and the energy management system DIN EN 50001.

The used materials meet the REACH default (EU regulation 1907/2006) and the RoHS default (EU guidelines 2011/65).

CoreTel s.r.o.
 K Cintorínu 64
 010 04 Žilina
 Slovenská republika

IČO: 47 744 731
 IČ DPH: SK2024077726

Fio banka a.s. č.ú.:
 EUR: 2500577171/8330
 CZK: 2100577172/2010
 USD: 2400577174/8330

Tel. č.: +421 948 87 55 87
 Tel. č.: +421 948 86 55 86
 Email: coretel@coretel.eu
 Web: www.coretel.eu