

- A360 aluminium alloy housing with weather-resistant protective powder coating
- Pressure test at 15psi for 60 seconds under water
- Patented 360 degrees 4 strong holding force seizures
- Operating temperature -40C - +60C



Type no.	ODT 4-08	ODT 4-11	ODT 4-14	ODT 4-17	ODT 4-20	ODT 4-23	ODT 4-26	ODT 4-29
Item no.	40408	40411	40414	40417	40420	40423	40426	40429
Insertion loss IN-OUT (5-500 MHz)	-	2.5 dB	1.7 dB	1.0 dB	0.9 dB	0.8 dB	0.7 dB	0.7 dB
Insertion loss IN-OUT (500-1000 MHz)	-	3.7 dB	2.4 dB	1.4 dB	1.2 dB	0.9 dB	0.9 dB	0.9 dB
Tap loss IN-TAP (5-500 MHz)	7.2 dB	11.8 dB	14.3 dB	18.2 dB	20.1 dB	23.6 dB	26.1 dB	29.2 dB
Tap loss IN-TAP (500-1000 MHz)	8.0 dB	11.5 dB	13.8 dB	17.6 dB	19.4 dB	22.6 dB	25.4 dB	29.2 dB
Isolation OUT-TAP (5-500 MHz)	-	33 dB	30 dB	35 dB	31 dB	34 dB	37 dB	39 dB
Isolation OUT-TAP (500-1000 MHz)	-	36 dB	29 dB	31 dB	29 dB	31 dB	32 dB	34 dB
Isolation OUT-OUT (5-500 MHz)	36 dB	28 dB	29 dB	39 dB	36 dB	38 dB	40 dB	44 dB
Isolation OUT-OUT (500-1000 MHz)	23 dB	33 dB	30 dB	27 dB	26 dB	25 dB	28 dB	31 dB
Return loss IN, OUT, TAP* (5-1000 MHz)	Cat. B	Cat. B	Cat. B	Cat. B	Cat. B	Cat. B	Cat. B	Cat. B
Max. Power passing	12A, 90VAC							
RFI	> 100 dB							
Connector IN, OUT	5/8"							
Connector TAP	F-female (ANSI/SCTE 01 2006)							
Dimensions	90.2 x 104 x 72 mm							
Weight	288 g							

**CoreTel s.r.o.**  
 K Cintorínu 64  
 010 04 Žilina  
 Slovenská republika

IČO: 47 744 731  
 IČ DPH: SK2024077726

Fio banka a.s. č.ú.:  
 EUR: 2500577171/8330  
 CZK: 2100577172/2010  
 USD: 2400577174/8330

Tel. č.: +421 948 87 55 87  
 Tel. č.: +421 948 86 55 86  
 Email: coretel@coretel.eu  
 Web: www.coretel.eu