

3M™ PBO Size 2 V2

Indoor/Outdoor FTTH Branching Point Box



**Distribution Box
PBO Size 2**

The **PBO Size 2** is designed for use as an indoor or outdoor FTTH branching point box for a maximum of 144 fusion splices. Equipped with the BPEO Evolution organiser, the box is also suitable for mechanical splices and PLC splitter management.

Product is suitable for building distribution

The PBO 2 is based on a standard box from the BDX 3000 range already extensively used worldwide.

The hinged cover can be removed from the base . This allows work to be carried out when the box is already installed in position.

The PBO size 2 is closed with a latch and may be secured with a locking device if required.

Content of the standard product:

- BDX3000 box size 2
- Organiser with 12 slots for trays
- Anchoring device for main cable and drop cable

Accessories

Splice trays and closure supports should be ordered separately.

Features	Benefits
<p>Versatile product for indoor or outdoor use</p> <p>Organiser with swivelling trays</p> <p>Anchoring device for main cable and drop cable</p> <p>Wall or pole installation</p> <p>Mid span access facility</p>	<p>One product matches all requirements</p> <p>Possible to reach each splice without disturbing other fibres</p> <p>Each cable is secured in place</p> <p>Possible to use in both indoor and outdoor locations</p>

Specification

General product features			Specification			
Connection	Capacity	Information	Degree of protection (EN 6 529)	IP 55 / IK06		
Mechanical splices *	72	6 or 12 splice trays				
Splitters 1 by 8	6	1 splitter & 9 splices in 2 slot tray				
Splitters 1 by 32	2					
Fusion splices						
High-density	144	12 splice trays 12 splices per tray				
* Fibrlok 4x4						
Installation:	Screws (4 x M6)		Dimensions (in mm)	without fixing supports		
				Length	Width	Depth
			BDX3000 T2B	400	255	86
			Color	Body Dark grey - RAL 7037 Cover Light grey - RAL 7035		
			Material	Thermoplastic		

Ordering information

Ref. No.

PBO box size 2 with 12 slot organiser	N501659A	501659
Fixing bracket for PBOs 2 units required for PBO size 2. Minimum Order Quantity: 4	N530171A	530171
BPEO-K7-1 SLOT-12 fusion Compatible with fusion splice protectors 45 or 60 mm long Splice tray is supplied with a cover	N541106A	541106
BPEO-K7-2 SLOT-12 fusion and PLC splitter Compatible with fusion splice protectors 45 or 60 mm long Can accommodate 70x10x6 mm PLC splitter Splice tray is supplied with a cover	N541104A	541104
BPEO-K7-1 SLOT-6 Fibrlok 2540G Compatible with mechanical splices Fibrlok 2540G Splice tray is supplied with a cover	N541103A	541103
BPEO-K7-2 SLOT-12 Fibrlok 2540G Compatible with mechanical splices Fibrlok 2540G Splice tray is supplied with a cover	N541108A	541108
BPEO-K7-2 SLOT-10 Fibrlok with Splitter Can accommodate 70x10x6 mm PLC splitter Splice holder for 10 Fibrlok 2540G Splice tray is supplied with a cover	N541110A	541110
Keylock Type 1242-E : Lock (MOQ= 10), 2 Keys (MOQ = 10)	NN36903100	
Cable Ties are not supplied	NN16955500	

Important Notice

The details contained in this literature have been carefully prepared from information available to 3M at the time of its production. However, it is not intended to be relied upon for purposes of product specification and you should contact your sales representative if specification details are required. Because of the wide variety of processes and conditions in which these products may be used, the user should first carry out tests to determine the suitability of the products for the particular use intended. All questions of warranty and liability relating to 3M products are governed by the selling 3M subsidiary's Terms of Sale subject where applicable to the prevailing law.
3M is trademark of the 3M company. SID is a trademark of Quante AG.



3M Telecommunications

Europe, Middle East & Africa
c/o 3M Deutschland GmbH
Carl-Schurz-Straße 1
41453 Neuss · Germany
Tel.: ++49 (0)2131 / 14-5999
Fax: ++49 (0)2131 / 14-5998
Internet: www.3MTelecommunications.com/eu

Rights reserved to make technical alternations.
Edition XX/2009