



SX288-5E-UTP-WH

SOLARIX CATEGORY 5E

SX108 and SX288 Wall Outlets

2.5/5 Gbps

100 MHz

Number of Ports	1 and 2 x RJ45
Min. Port Life	750 cycles
Contact Plating	50 µ gold and 100 µ nickel
Termination Module	110 8p8c
Min. Termination Module Life	200 cycles
Conductor Size and Type	AWG 26 – 22, solid
Housing Material	FR acc. to UL94-0
Colour	White
Dimensions	60 x 56 x 28 mm
Storage Temperature	-40 to +70 °C
Operational Temperature	-10 to +60 °C
Max. Operational Humidity	93 %

These wall-mount Solarix one-port and two-port outlets have an excellent performance and are offered in both unshielded and shielded versions. They easily exceed electrical parameters specified in the ANSI/TIA 568C.2, ISO/IEC 11801, and EN 50173 standards. Both T568A and T568B wiring configurations are supported on their 110 termination block. The SX108 and SX288 outlets come with red and blue port markers for each port allowing easy administration. The colour of the outlets is white.

Part No.

Description

SX108-5E-UTP-WH	Surface Mount Outlet Solarix Category 5E UTP 1 x RJ45 White
SX108-5E-STP-WH	Surface Mount Outlet Solarix Category 5E STP 1 x RJ45 White
SX288-5E-UTP-WH	Surface Mount Outlet Solarix Category 5E UTP 2 x RJ45 White
SX288-5E-STP-WH	Surface Mount Outlet Solarix Category 5E STP 2 x RJ45 White



SX108-5E-UTP-WH



SX108-5E-STP-WH

