

75 Ohm Coaxial Cable

PerfectFlex®
BROADBAND COAXIAL CABLE

P11ET77EPRM



General Description

11 Series, Perfect Prep®, Tri-shield, 77% Braid, Perfect Guard®, Black PE Jacket
Meter Marked, Reel Package

Mechanical Specifications

Specification	Value
Center Conductor	Copper-covered steel
Nominal Diameter	0.064" (1.63 mm)
Dielectric	Closed cell foamed polyethylene
Nominal Diameter Over Dielectric	0.280" (7.11 mm)

Shield Specifications

Specification	Value
1st Shield	APA-laminated tape bonded to dielectric
Nominal Diameter Over Tape	0.288" (7.29 mm)
2nd Shield	34 AWG aluminum braid wire; 77% coverage
3rd Shield	APA-laminated tape

Jacket Specifications

Specification	Value
Jacket	Black PE
Nominal Diameter Over Jacket	0.400" (10.16 mm)


Performance Specifications

Specification	Value
NEC Rated	None
Characteristic Impedance	75 +/- 3 Ohms
Nominal Velocity Propagation	82%

Packaging Specifications

Specification	Value
Cable Length per Reel	1,000 ft. (305 m)
Packaging Dimensions	18"x6"x11" (45.7x15x28 cm)
Shipping Weight per Reel	55lbs/1,000 ft

Unless otherwise specified, dimensions, material, electrical and mechanical specifications shall comply with ANSI SCTE 74 *Cable image for reference only. Please refer to jacket description for color.



Performance Specifications

Frequency (MHz)	Maximum (dB/100ft)	Maximum (dB/100m)
5	0.36	1.18
55	0.95	3.12
211	1.81	5.94
250	1.98	6.50
300	2.17	7.12
350	2.36	7.74
400	2.53	8.30
450	2.69	8.83
500	2.85	9.35
550	3.01	9.88
600	3.16	10.37
750	3.58	11.75
870	3.90	12.80
1000	4.23	13.88
1200	4.71	15.45
1450	5.29	17.36
1750	5.95	19.52

Attenuation (max corrected to 20°C)

